

1 - MINIHANDYLIGHT 10-35

cod. 494

Aluminium anticorodal anodized

Tempered glass float type Depth rating: 490 feet

Waterproof resistance by O rings Bulb type: alogen G4 6V, 10/20/35 W

Battery pack: NiCd interchangeable and water resistant

Time of charge (std. charge): 6 hours

Time of charge (optional automatic charger): 2 hours

Quartz treated reflecting element

Angle of light: 40° 1mt
Burn time with 10W: 45 min

ON/OFF with electromechanical switching

Size: lenght 158 mm, Ø 56 mm

Weight: 0,620 Kg (on air) - 0,100 Kg (underwater)

2 - HANDYLIGHT 10-35

cod. 495

Power supply: 6V, 3A Lamps: 10/20/35W Burn time: 40' (20W) Weight (in air): 0.7 Kg Weight (in water): 0.2 Kg Lenght: 200 mm, Ø 56 mm

The Handylight's reflecting group can be separated and connected by cable to its battery pack or to the

3 -SUPERHANDYLIGHT

10-35

cod. 496

Power supply: 12v, 3A Lamps: 10/20/35 W Burn time: 80' (20W) Weight (on air): 1.2 Kg Weight (underwater): 0.4 Kg Lenght: 285 mm, Ø 56 mm

The Handylight's reflecting group can be parted and connected by cable to its battery pack or to the real

4 - SUPERHANDYLIGHT 10-50

cod. 496 F



Material type	alluminium anticorodal anodized
front glass	tempered float glass
Depth use	150 mt "special type = 250 mt"
waterproof	by o rings
bulbs type	halogen G6 12V, 10/20/35/50 W
replace bulbs	

Unscrew screw and pullout bulbs group of the head -see picture-



batteries	12V- NiCd, 3A	
recharge time	6h / "optional automatic recharge battery	3h"

parabola	quartz	
light angle		
	40° at 1 mt.	
burn time with bulbs 20 W80'		
ON/OFF		
	with puhbotton electomechanical	
size		
	L 300 mm, Ø 56 mm	
weight		
	on air 1,200 Kg. / underwater 0,400 Kg.	