



Tecnical features Common features

MATERIAL TYPE: EXTRUDED ALUMINIUM ANODIZED
FRONT GLASS: 8MM THIGNESS TEMPERED
HANDLE/GRIP: REVERSIBLE, GUN/HANDLE TYPE

LB 20-60

cod. 593-A

Power supply: 12v, 3A
Lamps: 20 - 50 W
Burn time: 20' (50W)
Weight (on air): 1.8 Kg
Weight (underwater): 0.200 Kg
Lenght: 138 mm
Diameter: 100 mm

LB 20-180

cod. 693

CHECK BATTERY LEVEL: BY DIODE ON THE TOP GUIDE
ON OFF MODE: ELECTROMAGNETIC TYPE, NO PORT
BATTERY PACK: 10 AMP. NiMh INTERCHANGEABLE
BATTERY CONTROL: BY MINIATURIZED ELECTRONIC BOARD, TEMPERATURE/DISCHARGE
BULBS USABLE: ALOGEN G6 FROM 35/50/75/100/150W 3500°K
BURN TIME: 50WATT = 140 MINUTES
GAS SECURITY: MECHANICAL GAS VALVE
REFLECTING ELEMENTS WIDE LIGHT 80° - MEDIUM WIDE 40° - SPOT 10°
(QUARTZ TREATMENT)
USE: VIDEO/EXPLORATIONS
DEPTH RATING: 450 FEET

LH 20-180

cod. 793

Power supply: 12v, 10 A
Lamps: 20 - 150 W
Burn time: 80' (100W)
Weight (on air): 3,6 Kg
Weight (in water): 0,9 Kg with 5A battery pack
Length: 282 mm
Diameter: 100 mm